



Contents

PREFACE	State of the Art	5
CHAPTER 1	DEVICE CHARACTERISTICS	27
	Reverse Blocking Triode Thyristor-SCR	27
	Bidirectional Triode Thyristor—Triac	82
	Hockey-Puk SCRs	90
	Passivated Assembled Circuit Elements—PACE/paks	95
	General Application Hints	102
CHAPTER 2	PARALLEL OPERATION	113
	Important Characteristics	113
	Turn-On Sensitivity and Delay Time	114
	Finger Voltage	123
	Latching and Holding Current	125
	Steady-State Conditions	125
	Loop Inductance	126
CHAPTER 3	SERIES OPERATION	131
	Equalization	131
	Triggering Series-Operated SCRs	138
CHAPTER 4	AC PHASE CONTROL	149
	Phase Control Circuits	149
	Heater Control Circuits	167
	Ferroresonant Transformer Regulated AC Power Supply	182
	Motor Control Circuits	193
	Welding Service Circuits	195
CHAPTER 5	SOLID-STATE RELAYS AND CONTACTORS	203
	Solid-State Relays	203
	Solid-State Contactors	210
	Solid-State Switches	213
	Aircraft Power System	218
CHAPTER 6	DC POWER CONVERSION	231
	Biphase Circuits	231
	Single-Phase, Half-Wave Circuits	236
	Polyphase Rectifier Circuits	238
	Hybrid Circuits	241
	Triggering Pulses for Bridge Circuits	243
	DC Motor Drives	244
	Triac Reversing Drives	248
	PACE/pak Power Controls	250

CHAPTER 7	LINE-COMMUTATED INVERTERS	257
	Regenerative Phase-Controlled Rectifiers	257
	Brushless Motor Drives	262
	Cycloconverters	267
CHAPTER 8	FORCED-COMMUTATED INVERTERS	283
	Basic Circuits	283
	Frequency Multiplier	293
	DC Power Supplies	295
	Induction Heating Supply	301
	Variable Frequency Motor Drives	307
CHAPTER 9	CHOPPERS	313
	Switching Principles	313
	Commutation Circuits	315
	DC Motor Drives	320
	Battery Charger Design Example	339
CHAPTER 10	FAST RECOVERY DIODES	345
	High-Frequency Power Rectification	345
	Recovery Characteristics	349
	Schottky Barrier Diodes	359
CHAPTER 11	PROTECTION	367
	Protecting with Fuses	367
	Protecting by Limiting Peak Junction Temperature.	384
CHAPTER 12	COOLING	393
	Thermal Considerations for Stud-Mounted Devices	393
	Thermal Considerations for Hockey-Puk Devices	397
	Cooling for Specific Applications	402
	Oil-Immersed Cooling	403
CHAPTER 13	TESTING	409
	Parameter 1: Blocking Voltage	409
	Parameter 2: On-State Voltage	411
	Parameter 3: DC Triggering Characteristics	414
	Parameter 4: Holding Current	416
	Parameter 5: Latching Current	422
	Parameter 6: Turn-On Time	428
	Parameter 7: Turn-On Voltage	428
	Parameter 8: Turn-Off Time	429
	Parameter 9: Critical dv/dt	443
	Parameter 10: Critical di/dt	448
	Parameter 11: Thermal Resistance	450
	Testing Power Triacs	453
	Triggering Circuits	462
APPENDIX I	SYMBOLS AND TERMS	471

SCR Applications Handbook

Edited by
Dr. Richard G. Hoft
Professor of Electrical Engineering
University of Missouri at Columbia

Contributors: The Engineering Staff of International Rectifier

Bryan Bixby
David Borst
Larry Carver
Arthur Connolly

F.W. Parrish
Ralph Rosa

David Cooper
Frank Durnya
John Gault
M. Frank Gift

1st Printing; September 1974

ACKNOWLEDGEMENTS

This handbook is the result of the efforts of a dedicated group of engineers. Not only those at International Rectifier, but also in numerous laboratories and factories throughout the world — a group of people we commonly refer to as our customers. Without our customers, the insight into the broad range of applications discussed in this book would be impossible.

Although this handbook is primarily intended for circuit and systems engineers, we hope it will also be found useful by educators, students and others interested in the use of semiconductor devices.

Information furnished in this Applications Handbook is believed to be accurate and reliable. However, International Rectifier can assume no responsibility for its use; nor any infringement of patents, or other rights of third parties which may result from its use. No license is granted by implication or other use under any patent or patent rights of International Rectifier. No patent liability shall be incurred for the use of the circuits or devices described herein.

Copyright, International Rectifier Corp., Semiconductor Division, El Segundo, California, 1974. All Rights Reserved.